



**RESUBMITTED SECTION OF CLAIMS PER**  
**NOTICE OF NON-COMPLIANT AMENDMENT**

**[Deleted material is struck-through and added material is underlined]**



1. (Currently Amended) An electrolyzer for the separation of water comprising:  
an aqueous electrolytic solution comprising water, the aqueous electrolyte solution  
partially filling an electrolysis chamber such that a gas reservoir region is formed above the  
aqueous electrolyte solution, said chamber being adapted to be installed in a closed pressurized  
piping system;

port means for adding the aqueous electrolytic solution to the chamber during operation  
of said electrolyzer when said electrolyzer is installed and used in said closed pressurized piping  
system;

two flat principal electrodes comprising an anode electrode and a cathode electrode, the  
two principal electrodes being at least partially immersed in the aqueous electrolyte solution;

one or more flat supplemental electrodes at least partially immersed in the aqueous  
electrolyte solution and interposed between the two principal electrodes wherein the two  
principal electrodes and the one or more flat supplemental electrodes are held in a fixed spatial  
relationship, and wherein the one or more flat supplemental electrodes are not connected  
electrically to a power source;

for each flat supplemental adjacent electrodes, one is made of a ~~meshed~~ **high porosity**  
**foam based** material made substantially of a nickel material and the opposing electrode is made  
substantially of a stainless steel material, wherein said meshed supplemental electrodes results in  
a (+) and (-) electrical (ionic) current flow that causes the formation of a single combustible gas  
over an entire surface area of both sides of all electrodes within the electrolyzer;

one or more external fins serving as a heat sink for removing heat from the electrolyzer;  
and

said electrolyzer being adapted to separate the water such that its constituents of H and O  
are not recombined and instead produced jointly to make the single combustible gas composed of  
combinations of magnetically bonded clusters of hydrogen and oxygen atoms structured  
according to a general formula  $H_mO_n$  wherein m and n have null or positive integer values with  
the exception that m and n can not be 0 at the same time,

wherein said combustible gas has a varying energy content depending on its use.

2. (Previously Presented) The electrolyzer according to claim 1, wherein said combustible gas contains atomic hydrogen.

3. (Previously Presented) The electrolyzer according to claim 1, wherein said combustible gas contains atomic oxygen.

4. (Previously Presented) The electrolyzer according to claim 1, wherein the combustible gas instantly melts solids.

5. (Previously Presented) The electrolyzer according to claim 1, wherein the combustible gas can be used as a fuel without the need of atmospheric oxygen.

6. (Previously Presented) The electrolyzer according to claim 1, wherein the combustible gas can bond to combustible fuels via magnetic induction.

7. (Canceled)

8. (Previously Presented) The electrolyzer according to claim 1, wherein when said combustible gas is used as an additive to a combustible fuel, a combustion of said fuel having said additive results in an exhaust emission having less pollutants than a combustion of said fuel alone.

9. – 50. (Canceled)

51. (Previously Presented) The electrolyzer according to claim 1, wherein each adjacent electrodes are spaced-apart from each other by a distance of about 0.15 inches to about 0.35 inches.

52. (New) An on-demand self-producing combustible gas electrolyzer system for the separation of water into a combustible gas for use in combustion equipment, such as welder and combustion engines, the electrolyzer system comprising:

an electrolyte reservoir having a top portion adapted to contain a generated combustible gas and a bottom portion containing electrolytic fluid comprising water;

an electrolyzer, said electrolyzer being installed in a closed pressurized portion of the system;

said electrolyzer having two flat principal electrodes comprising an anode electrode and a cathode electrode, the two principal electrodes being at least partially immersed in an aqueous electrolyte solution within the electrolyzer;

one or more flat supplemental electrodes at least partially immersed in the aqueous electrolyte solution and interposed between the two principal electrodes wherein the two principal electrodes and the one or more flat supplemental electrodes are held in a fixed spatial relationship, and wherein the one or more flat supplemental electrodes are not connected electrically to a power source;

for each flat supplemental adjacent electrodes, one is made of a high porosity foam based material made substantially of a nickel material and the opposing electrode is made substantially of a stainless steel material, wherein said meshed supplemental electrodes results in a (+) and (-) electrical (ionic) current flow that causes the formation of a single combustible gas over an entire surface area of both sides of all electrodes within the electrolyzer;

a pump fluidly interposed between the bottom of the electrolyte reservoir and the electrolyzer wherein the pump draws electrolytic fluid from the electrolyte reservoir and pumps it to the electrolyzer;

a radiator fluidly connected to and interposed between the electrolyzer and the electrolyte reservoir, the radiator adapted to cool the generated combustible gas before returning to the top portion of the electrolyte reservoir;

an interstitial space within the reservoir above the electrolytic fluid in the top portion of the electrolytic reservoir wherein the generated combustible gas accumulates; and

at least one dryer/filter means through which the generated combustible gas passes before being drawn as needed for use,

wherein the electrolyzer is adapted to separate water such that its constituents of H and O are not recombined and instead produced jointly to make a combustible gas composed of combinations of magnetically bonded clusters of hydrogen and oxygen atoms structured according to a general formula  $H_mO_n$  wherein m and n have null or positive integer values with the exception that m and n can not be 0 at the same time, said produced gas being stable and nonvolatile, and

wherein said combustible gas has a varying energy content depending on its use.

53. (New) The electrolyzer system according to claim 52, wherein said combustible gas contains atomic hydrogen.

54. (New) The electrolyzer system according to claim 52, wherein said combustible gas contains atomic oxygen.

55. (New) The electrolyzer system according to claim 52, wherein the combustible gas instantly melts solids.

56. (New) The electrolyzer system according to claim 52, wherein the combustible gas can be used as a fuel without the need of atmospheric oxygen.

57. (New) The electrolyzer system according to claim 52, wherein the combustible gas can bond to combustible fuels via magnetic induction.

58. (New) The electrolyzer system according to claim 52, wherein when said combustible gas is used as an additive to a combustible fuel, a combustion of said fuel having said additive results in an exhaust emission having less pollutants than a combustion of said fuel alone.